

Model 7 Spray Gun

Model 7

The Model 7 spray gun is used for all production spraying, but is recommended primarily for siphon use with the Binks 81-810 1 quart Drip-Proof cup.

Drop forged aluminum body. Large air passages. Plated drop forged brass head. Adjustable floating fluid needle valve. Stainless steel air valve cartridge. Controls at back of gun. Adjustable spray pattern.



Technical Specifications:

Body:	Drop-forged anodized aluminum
Weight:	28 Oz.
Air Inlet:	1/4" NPS (M)
Fluid Inlet:	3/8" NPS (M)
Feed Type:	Pressure/Siphon Feed
Part Sheet:	77-1153
Gun Repair Kit:	6-188

Most Popular Nozzle Set Ups:

7 Gun	36SS x 36SD
7 Gun	36SS x 36SK

Standard Fluid Nozzle and Needle are 303 Stainless Steel

Model 7 Gun Nozzle and Needle Selection Chart

Type of Fluid	Fluid x Air Nozzles	Type	CFM at			Max Pattern At 8"	Fluid Needle ■	Air Nozzle Retaining Ring
			30 PSI	50 PSI	70 PSI			
THIN								
Lacquers, Sealers	33SS x 33PM	Pressure	10.1	15.0	20.0	10"	33	54-704*
Stains, Primers	36SS x 36SD	Siphon	7.8	11.5		10"	36	▲
Zinc Chromates								
MEDIUM								
Lacquers, Enamels	36SS x 36SD	Siphon	7.8	11.5		10"	36	▲
Varnishes, Shellacs	36SS x 36SK	Siphon	11.5	15.7	20.2	13"	36	▲
Primers, Epoxies								
Urethanes,								
MEDIUM HEAVY								
House Paints	38SS x 38PM	Pressure	9.3	14.9	20.0	10"	38	▲
Multi-colors								
Wrinkles								

* Not furnished with nozzle. Please order separately. ▲ Furnished with nozzle. ■ All fluid needles are stainless steel..
Fluid nozzle orifice sizes - 33SS = .040 36SS = .070 38SS = .086