

# EGHV™ Touch-Up Maximum Performer

## HVLP Spray Gun



For gun, cap and tip information see charts on pages 15 & 17.

Comfortable and easy-to-use, the EGHV Touch-Up Maximum Performer spray gun provides precise control for the most exacting detail and touch-up work. The gun features a long tapered fluid needle and a top-mounted trigger, and weighs only 7.5 ounces, making it ideal for hours of fatigue-free precision painting.

- Fluid delivery by attached suction feed or remote pressure feed cup.
- Knurled knobs for fine adjustments of fluid flow and spray pattern.

### Productivity and Finish Quality

The productivity and finish quality of any Maximum Performer spray gun is determined by the air cap and fluid tip combination. The chart on page 17 provides detailed information about the solids range, fluid flow and air consumption, and also illustrates the spray pattern.

### Ordering Information

The EGHV Touch-Up Maximum Performer manual spray gun is available with the following air cap and fluid tip set-up, factory assembled for immediate delivery.

Part No.

EGHV-531-397E \*

\* Standard tip and needle is stainless steel.

### EGHV Accessories

- **8 oz. Cup (TGS-503)**  
Solvent-resistant polyethylene cup available.
- **Remote Cups**  
Two-quart remote cups are available in aluminum (KB-555) or stainless steel (KB-545-SS).
- **Additional Accessories**  
Hose assemblies, air cap test kit, gun and hose cleaning equipment and other accessories also are available.

### Technical Specifications

Body:	Drop forged aluminum
Weight:	7.5 oz (210 gr)
Air Inlet:	1/4" NPS (M)
Fluid Inlet:	1/4" NPS (M)
Fluid Passages:	Stainless Steel
Feed Type:	Pressure feed Suction feed
Air Consumption:	8.8 CFM max. @ 10 psi cap pressure
Air Cap Pressure:	10 psi @ 50 psi inlet
Service Bulletin:	SB-2-167
Gun Repair Kit:	KK-5044



EGHV-531 gun and TGS-503 translucent polyethylene cup provide a precision finish with less overspray.