



Maverick™ Air Spray Gun

Compact design delivers optimum performance, superior atomization for today's demanding finishing requirements.

The compact Maverick Air Spray gun provides superior atomization for optimum performance in demanding liquid painting production applications. The spray gun can be used with a variety of coatings on a range of substrates from wood to metal and glass. The spray gun's lightweight, ergonomic design, easy trigger pull, and single-knob fan adjustment reduce fatigue for maximum operator efficiency.



Maverick™ Air Spray Gun

Variety of Fluid Tips, Needles, and Air Caps

Each Maverick gun is shipped standard with a 1.1-mm fluid tip, needle, and precision-machined air cap combination. Additional siphon-feed and pressure-feed air cap kits are available to expand the capabilities of the gun. With these options, the Maverick gun can spray a variety of coatings ranging from low-viscosity, automotive-type base coat and clear coats, as well as high-solids solvent and waterbased coatings. A stainless-steel fluid tip also enables the Maverick gun to spray waterborne coatings.

Excellent "Out of Box" Performance

To assure the ready-to-spray performance and quality of the spray gun, every Maverick gun is tested prior to shipment for excellent "Out of box" performance.

Guarantee in a Box

Each Maverick spray gun is shipped with a set of replacement wear items including O-rings, seals, and packings. The additional parts allow the operator to complete simple maintenance to the gun without lengthy downtime.

Features and Benefits

- **Convenient, built-in cheater valve** for greater air pressure control
- **Stainless-steel fluid passages** accommodate a variety of coatings
- **Lightweight, ergonomic design and easy trigger pivot** reduce operator fatigue
- **Hardened, stainless-steel needle** for longer life and lower maintenance costs
- **Self-adjusting packings**
- **Variety of nozzle configurations available** for maximum flexibility to spray wide range of materials

Specifications

Weight:	339 grams
Air Inlet Size:	1/4-in. NPS
Fluid Inlet Size:	3/8-in. NPS
Maximum Air Pressure:	43 psi

Nordson reserves the right to make design changes to products to improve their function. These changes may occur between printings.

For more information, talk with your Nordson representative or contact your Nordson regional headquarters office.

United States

Amherst, Ohio
Nordson Corporation
Telephone: 800.433.9319
440.988.9400
Facsimile: 888.229.4580
E-mail: maverickinfo@nordson.com

www.nordson.com

Canada

Markham, Ontario
Nordson Canada, Limited
Telephone: 800.463.3200
905.475.6730
Facsimile: 905.475.8821
www.nordson.ca

www.nordson.ca

Europe

Erkrath, Germany
Nordson Deutschland GmbH
Telephone: 49.211.9205.0
Facsimile: 49.211.254658
E-mail: info@de.nordson.com

Japan

Tokyo, Japan
Nordson K.K.
Telephone: 81.3.5762.2700
Facsimile: 81.3.5762.2701
E-mail: ppa.dm@nordson.co.jp

www.nordson.co.jp

Asia/Australia/Latin America

Nordson Corporation
Amherst, Ohio
Telephone: 440.985.4000
24-hour message service:
440.985.4797
E-mail: intcustomerservice@nordson.com