



# Maverick™ HVLP Spray Gun

*Lightweight Maverick HVLP spray gun delivers optimum performance, superior atomization for today's demanding finishing requirements.*

The lightweight Maverick HVLP (high volume, low pressure) spray gun provides superior atomization for optimum performance in today's demanding liquid painting production applications. The spray gun can be used with a variety of coatings on a wide range of substrates from wood to metal and glass. The spray gun's lightweight, ergonomic design, easy trigger pull, and single knob fan adjustment reduce operator fatigue for maximum operating efficiency.



Maverick™ HVLP Spray Gun

## Variety of Fluid Tips, Needles, and Air Caps

Each Maverick gun is shipped standard with a 1.0-mm fluid tip, needle, and precision-machined air cap combination. Additional siphon-feed and pressure-feed air cap kits and HVLP compliance kits are available to expand the gun's capabilities. With these options, the Maverick can spray a variety of coatings ranging from low-viscosity, automotive-type base coat and clear coats, as well as high-solids, solvent and waterbased coatings. A stainless-steel fluid tip also enables the Maverick gun to spray waterborne coatings.

## Excellent "Out of Box" Performance

To assure the ready-to-spray performance and quality of the spray gun, every Maverick gun is tested prior to shipment for excellent "Out of box" performance.

## Guarantee in a Box

Each Maverick spray gun is shipped with a set of replacement wear items including O-rings, seals, fittings, and packings. The additional parts allow the operator to complete simple maintenance to the spray gun without lengthy downtime.

## Features and Benefits

- **Built-in, cheater valve** for greater air pressure control
- **Stainless-steel fluid passages** accommodate a variety of coatings
- **Lightweight design and easy trigger pivot** reduce operator fatigue
- **Hardened, stainless-steel needle** for longer life and lower maintenance costs
- **Self-adjusting packings**
- **Variety of nozzle configurations available** for maximum flexibility to spray wide range of materials

## Specifications

Weight: 558 grams  
 Air Inlet Size: 1/4-in. NPS  
 Fluid Inlet Size: 3/8-in. NPS  
 Maximum Air Pressure: 43 psi

Nordson reserves the right to make design changes to products to improve their function. These changes may occur between printings.

For more information, talk with your Nordson representative or contact your Nordson regional headquarters office.

### United States

Amherst, Ohio  
 Nordson Corporation  
 Telephone: 800.433.9319  
 440.988.9400  
 Facsimile: 888.229.4580  
 E-mail: maverickinfo@nordson.com

[www.nordson.com](http://www.nordson.com)

### Canada

Markham, Ontario  
 Nordson Canada, Limited  
 Telephone: 800.463.3200  
 905.475.6730  
 Facsimile: 905.475.8821  
[www.nordson.ca](http://www.nordson.ca)

[www.nordson.ca](http://www.nordson.ca)

### Europe

Erkrath, Germany  
 Nordson Deutschland GmbH  
 Telephone: 49.211.9205.0  
 Facsimile: 49.211.254658  
 E-mail: info@de.nordson.com

### Japan

Tokyo, Japan  
 Nordson K.K.  
 Telephone: 81.3.5762.2700  
 Facsimile: 81.3.5762.2701  
 E-mail: ppa.dm@nordson.co.jp

[www.nordson.co.jp](http://www.nordson.co.jp)

### Asia/Australia/Latin America

Nordson Corporation  
 Amherst, Ohio  
 Telephone: 440.985.4000  
 24-hour message service:  
 440.985.4797  
 E-mail: [intcustomerservice@nordson.com](mailto:intcustomerservice@nordson.com)